How to setup cFos Outlook DAV

Etape 1

Run the cFos Outlook DAV installer to add cFos Outlook DAV as Outlook Add-in. It is tested with Outlook 2013, but should also work with Outlook 2010.

Etape 2

Start Outlook and create a new calendar folder. The name must begin with “caldav” (case insensitive), for example “caldav_google”, “caldavpnet” or “CalDAV-DAViCal”.

Etape 3

```
   As soon as the folder is created, please restart Outlook. Now a little
setup dialog should pop up.
   Select the config file corresponding to your newly created Outlook folder
and enter the URL of your CalDAV calendar server, your username and
password.
   You can also specifiy the sync-interval. Then restart Outlook one more
time.
```

CalDAV URL for cFos Personal Net

For cFos Personal Net the CalDAV URL is http://your_pnet_domain/private/your_user_name/caldav_personal, where your_pnet_domain is the domain or IP address of your cFos Personal Net server or localhost or a local IP address in your LAN. your_user_name is the name of owner of the calendar, e.g. admin. So we supposed (not tested) that in our case we have to put : https://webmail.ias.u-psud.fr/private/your_user_name/caldav_personal

---

URL for Google Calendar

For Google Calendar the URL is https://www.google.com/calendar/dav/your_google_calendar_id/events (make sure that your URL is of the “https” protocol, because “http” addresses will not work).

you_google_calendar_id for your primary calendar is your Google email address. However, for all other calendars, the calendar ID has the format [long_string]@group.calendar.google.com. You can retrieve the calendar ID at calendar.google.com by clicking on the “down” arrow next to your calendar and selecting “Calendar settings”. As user name and password use the same information as for other Google services. For further information you might consider having a look at our detailed illustrated instructions .

URL for DAViCal calendar

For a DAViCal calendar the URL is http://your_davical_server/caldav.php/your_davical_account/calendar, where your_davical_server is the domain or IP address of your DAViCal server. your_davical_account is the username for your calendar and the password is the one assigned to this user.

---

cFos Outlook DAV operation

When you start Outlook, cFos Outlook DAV tries to synchronize all calendar events of your Outlook CalDAV folder with the CalDAV server. If something on the server has changed, the changes are reflected in your Outlook folder. So events added or modified on the server will be added or modified in your local folder. Event deleted on the server will be deleted in your local folder. This synchronisation is done every n minutes depending on the sync interval you specified in the folder setup. Whenever you add, change or delete an event in your local folder cFos Outlook DAV will immediately try to update the server. The folder configuration data is stored in the directoryc:\users\your_username\appdata\local\cfos\outlook_dav. The directoryc:\programdata\cfos\outlook_dav contains folder_setup.hta, so you can later change your configuration. Passwords are stored with a preceding “!” and encrytped on-the-fly as soon as cFos Outlook DAV needs them. In c:\programdata\cfos\outlook_dav you also find a file trace.txt with a log of the last recent sync operations.

From:
https://docinfo.ias.u-psud.fr/ - **Informations, recommandations et conseils du service informatique de l'IAS**

Permanent link:
https://docinfo.ias.u-psud.fr/doku.php/synchronisation_outlook?rev=1406192998

Last update: **2014/07/24 09:09**